

9/12/16



Safety Data Sheet:  
Material Name: Elmer's No-Wrinkle  
Rubber Cement  
SDS ID: SDS-34  
Issue Date: 2016-06-03  
Revision: 2.3

ELMER'S No-Wrinkle  
Rubber Cement

**Other Sections**

01020304050607080910111213141516

**Section 1 - PRODUCT AND COMPANY IDENTIFICATION**

**Material Name**

Elmer's No-Wrinkle Rubber Cement

**Synonyms**

E141; E904; 231, 232, 233, 234, 61518; E63231T; E425; E1539, 60818

**Chemical Family**

Adhesive

**Product Use**

Adhesive

**Details of the supplier of the safety data sheet**

Elmer's Products, Inc  
460 Polaris Parkway, Suite 500  
Westerville, OH 43082  
USA  
Phone:1-888-435-6377  
Fax:1-800-741-6046  
Email:comments@elmers.com

**Emergency Phone Number:**

Poison Control Center  
1-888-516-2502

For additional product information, access our website at [www.elmers.com](http://www.elmers.com). To place an order, call 1-800-848-9400.


**Section 2 - HAZARDS IDENTIFICATION**

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

- Flammable Liquids - Category 2
- Aspiration Hazard - Category 1
- Skin Corrosion/Irritation - Category 2
- Serious Eye Damage/Eye Irritation - Category 2A
- Specific Target Organ Toxicity - Single Exposure - Category 3
- Specific Target Organ Toxicity - Repeated Exposure - Category 2
- Hazardous to the Aquatic Environment - Acute - Category 1
- Hazardous to the Aquatic Environment - Chronic - Category 1

**GHS Label Elements**

**Symbol(s)**



**Signal Word**

Danger

**Hazard Statement(s)**

Highly flammable liquid and vapor.  
 May be fatal if swallowed and enters airways.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause respiratory irritation. May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
 Very toxic to aquatic life with long lasting effects.

**Precautionary Statement(s)**

**Prevention**

Keep container tightly closed.  
 Keep away from heat/sparks/open flame/hot surfaces - No smoking.  
 Ground/Bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting equipment.  
 Take precautionary measures against static discharge.  
 Use only non-sparking tools.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not breathe dust/fume/gas/mist/vapours/spray.  
 Wash thoroughly after handling.  
 Avoid release to the environment.

**Response**

In case of fire: Use appropriate media to extinguish.  
 Collect spillage.  
 IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
 Call a POISON CENTER or doctor if you feel unwell.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If skin irritation occurs: Get medical advice/attention.  
 Take off contaminated clothing and wash before reuse.  
 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 Do NOT induce vomiting.  
 Specific treatment (see label).

**Storage**

Store in a well-ventilated place. Keep container tightly closed.  
 Keep cool.  
 Store locked up.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

| CAS      | Component Name | Percent |
|----------|----------------|---------|
| 142-82-5 | n-Heptane      | > 85    |

**Section 4 - FIRST AID MEASURES**

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

**Skin**

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Ingestion**

Immediately call a POISON CENTER or doctor/physician. DO NOT induce vomiting. Aspiration hazard. If vomiting occurs, keep head lower than hips to help prevent aspiration. Aspiration into the lungs may result in pulmonary edema and pneumonitis.

**Most Important Symptoms/Effects**

**Acute**

May be fatal if swallowed and enters airways. May cause respiratory irritation, skin irritation, eye irritation.

**Delayed**

May cause damage to organs through prolonged or repeated exposure.

## Section 5 - FIRE FIGHTING MEASURES

**Extinguishing Media**

**Suitable Extinguishing Media**

Dry chemical, foam or carbon dioxide, water.

**Unsuitable Extinguishing Media**

None known.

**Special Hazards Arising from the Chemical**

Highly flammable liquid and vapor. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Vapor/air mixtures are explosive.

**Advice for firefighters**

Wear self-contained breathing apparatus with a full facepiece and protective clothing.

**Fire Fighting Measures**

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Do not scatter spilled material with high-pressure water streams. In case of fire and/or explosion do not breathe fumes. Stay upwind and keep out of low areas.

## Section 6 - ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment and Emergency Procedures**

Keep unnecessary people away, isolate hazard area and deny entry. Do not breathe gas/vapor/spray. Avoid contact with eyes and skin. Vapors may cause drowsiness and dizziness. Wear personal protective clothing and equipment, see Section 8.

**Methods and Materials for Containment and Cleaning Up**

Eliminate all ignition sources if safe to do so. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Stop leak if possible without personal risk. Reduce vapors with water spray. Ground any equipment used in handling. Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material and transfer to container. Use only non-sparking tools. Large spills: Dike for later disposal.

**Environmental Precautions**

Prevent entry into waterways, sewers, basements, or confined areas. Avoid release to the environment. Collect spillage.

## Section 7 - HANDLING AND STORAGE

**Precautions for Safe Handling**

Avoid contact with eyes and skin. Do not breathe dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid heat, flames, sparks and other sources of ignition. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

**Conditions for Safe Storage, Including any Incompatibilities**

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

**Incompatible Materials**

acids, bases, amines, oxidizing materials.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**Component Exposure Limits**

|                  |  |
|------------------|--|
| <b>n-Heptane</b> | <b>142-82-5</b>  |
| ACGIH:           | 400 ppm TWA  |
|                  | 500 ppm STEL   |
| NIOSH:           | 85 ppm TWA ; 350 mg/m <sup>3</sup> TWA                           |
|                  | 440 ppm Ceiling 15 min ; 1800 mg/m <sup>3</sup> Ceiling 15 min   |
|                  | 750 ppm IDLH   |
| Europe:          | 500 ppm TWA ; 2085 mg/m <sup>3</sup> TWA                         |
| OSHA (US):       | 500 ppm TWA ; 2000 mg/m <sup>3</sup> TWA                         |
| Mexico:          | 400 ppm TWA LMPE-PPT ; 1600 mg/m <sup>3</sup> TWA LMPE-PPT       |
|                  | 500 ppm STEL [LMPE-CT ] ; 2000 mg/m <sup>3</sup> STEL [LMPE-CT ] |
|                  | Skin - potential for cutaneous absorption                        |

**EU - Occupational Exposure (98/24/EC) - Binding Biological Limit Values and Health Surveillance Measures**

There are no biological limit values for any of this product's components.

**ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)**

There are no biological limit values for any of this product's components.

**Engineering Controls**

Use explosion-proof electrical/ventilating/lighting equipment. Ensure compliance with applicable exposure limits.

**Individual Protection Measures, such as Personal Protective Equipment**

**Eye/face protection**

Wear chemical safety goggles.

**Skin Protection**

Wear appropriate chemical resistant clothing.

**Respiratory Protection**

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

**Glove Recommendations**

Wear appropriate chemical resistant gloves.

**Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

|                              |                         |                                  |                |
|------------------------------|-------------------------|----------------------------------|----------------|
| <b>Appearance</b>            | opaque liquid           | <b>Physical State</b>            | liquid         |
| <b>Odor</b>                  | mild odor ,solvent odor | <b>Color</b>                     | Not available  |
| <b>Odor Threshold</b>        | Not available           | <b>pH</b>                        | Not available  |
| <b>Melting Point</b>         | Not available           | <b>Boiling Point</b>             | 90 °C          |
| <b>Freezing point</b>        | Not available           | <b>Evaporation Rate</b>          | <1 (ether =1 ) |
| <b>Boiling Point Range</b>   | Not available           | <b>Flammability (solid, gas)</b> | Flammable      |
| <b>Autoignition</b>          | Not available           | <b>Flash Point</b>               | -4 °C (TCC )   |
| <b>Lower Explosive Limit</b> | Not available           | <b>Decomposition temperature</b> | Not available  |
| <b>Upper Explosive Limit</b> | Not available           | <b>Vapor Pressure</b>            | Not available  |

|                       |                  |  |               |
|-----------------------|------------------|--|---------------|
| Vapor Density (air=1) | >1               | Specific Gravity (water=1)             | 0.71          |
| Water Solubility      | almost insoluble | Partition coefficient: n-octanol/water | Not available |
| Viscosity             | Not available    | Solubility (Other)                     | Not available |
| Density               | Not available    | Volatility                             | 90 %          |
| Molecular Weight      | Not available    |  |               |

## Section 10 - STABILITY AND REACTIVITY

### Reactivity

No hazard expected.

### Chemical Stability

Stable under normal conditions of use.

### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Containers may rupture or explode if exposed to heat.

### Incompatible Materials

acids, bases, amines, oxidizing materials.

### Hazardous decomposition products

oxides of carbon.

## Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

#### Inhalation

May cause respiratory irritation.

#### Skin Contact

Causes skin irritation.

#### Eye Contact

Causes serious eye irritation.

#### Ingestion

Aspiration hazard. May be fatal if swallowed.

#### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

#### n-Heptane (142-82-5)

Oral LD50 Mouse 5000 mg/kg

Dermal LD50 Rabbit 3000 mg/kg

Inhalation LC50 Rat 103 g/m<sup>3</sup> 4 h

#### Immediate Effects

May cause respiratory irritation, skin irritation, eye irritation. May be fatal if swallowed.

#### Delayed Effects

May cause damage to organs through prolonged or repeated exposure.

#### Irritation/Corrosivity Data

Causes skin irritation. May cause eye irritation. May cause respiratory irritation.

#### Respiratory Sensitization

No information available for the product.

#### Dermal Sensitization

No information available for the product.

#### Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

#### Germ Cell Mutagenicity

No information available for the product.

**Tumorigenic Data**

No data available

**Reproductive Toxicity**

No information available for the product.

**Specific Target Organ Toxicity - Single Exposure**

Respiratory system

**Specific Target Organ Toxicity - Repeated Exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

May be fatal if swallowed.

**Medical Conditions Aggravated by Exposure**

No data available.

|  |
|--|
| <b>Section 12 - ECOLOGICAL INFORMATION</b> |
|--|

**Component Analysis - Aquatic Toxicity**

|           |                                 |
|-----------|---------------------------------|
| n-Heptane | 142-82-5                        |
| Fish:     | LC50 96 h Cichlid fish 375 mg/L |

|   |
|---|
| <b>Section 13 - DISPOSAL CONSIDERATIONS</b> |
|---|

**Disposal Methods**

Dispose in accordance with all applicable regulations.

**Component Waste Numbers**

|           |                   |
|-----------|-------------------|
| n-Heptane | 142-82-5          |
| RCRA:     | waste number D001 |
|           | waste number D001 |
|           | D001              |

|   |
|---|
| <b>Section 14 - TRANSPORT INFORMATION</b> |
|---|

**Component Marine Pollutants**

This material contains one or more of the following chemicals required by US DOT to be identified as marine pollutants

| Component | CAS #    | Minimum Concentration                                       |
|-----------|----------|---|
| n-Heptane | 142-82-5 | DOT regulated marine pollutant (related to Heptane isomers) |

**US DOT Information:****Shipping Name:** ADHESIVES**Hazard Class:** 3**UN/NA #:** UN1133**Packing Group:** I**Required Label(s):** 3**IATA Information:****Shipping Name:** ADHESIVES**Hazard Class:** 3**UN#:** UN1133**Packing Group:** I**Required Label(s):** 3**IMDG Information:**

**Shipping Name:** ADHESIVES  
**Hazard Class:** 3  
**UN#:** UN1133  
**Packing Group:** I  
**Required Label(s):** 3

**TDG Information:**  
**Shipping Name:** ADHESIVES  
**Hazard Class:** 3  
**UN#:** UN1133  
**Packing Group:** I  
**Required Label(s):** 3

### Section 15 - REGULATORY INFORMATION

#### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

|           |  |
|-----------|--|
| n-Heptane | 142-82-5   |
| TSCA 12b: | Section 4, 1 % de minimus concentration (related to Hydrocarbons, C>4) |

#### SARA Section 311/312 (40 CFR 370 Subparts B and C)

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

#### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

| Component | CAS      | CA  | MA  | MN  | NJ  | PA  |
|-----------|----------|-----|-----|-----|-----|-----|
| n-Heptane | 142-82-5 | Yes | Yes | Yes | Yes | Yes |

#### Not listed under California Proposition 65

#### Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

|           |          |
|-----------|----------|
| n-Heptane | 142-82-5 |
|           | 1 %      |

#### Component Analysis - Inventory

##### n-Heptane (142-82-5)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  | TW  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | Yes | Yes |

### Section 16 - OTHER INFORMATION

#### HMIS Rating

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

#### Summary of Changes

Updated SDS: 7/17/2015

#### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA -

Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; JP - Japan; Kow - Octanol/water partition coefficient; KECI - Korea Existing Chemicals Inventory; KECL - Korea Existing Chemicals List; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act.; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

**Other Information****Disclaimer:**

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.